Sprint[™] 6H and Sprint[™] 6H PLUS Clinical Centrfuges









The Sprint™ 6H and 6H PLUS are compact clinical centrifuges that include a six position, swing-out rotor. Prior to centrifugation, tubes are loaded vertically. Once the centrifuge starts, tubes swing to a horizontal position, providing the flat-line separation that is commonly preferred for further analysis.

The Sprint 6H centrifuge is designed for use with 10ml blood collection tubes (16x100mm), while smaller tubes (12 x 75/100mm) can be centrifuged with the use of optional adapters. The Sprint 6H PLUS model features a larger chamber/rotor and has the added capability of centrifuging tubes up to 15ml.



- Includes 6 place swing out rotor
- igspace+ Accepts blood tubes up to 10ml
- Ideal for Coag, PPP and urinalysis
- Locking Lid and digital timer

Technical Data (Sprint 6H):

Speed Range:	3,400 rpm / 1,600 xg
Capacity:	6 x 10ml 6 x 5-7ml (13mm)
Speed Increment:	Fixed
Timer:	30 mins. (1 min increments)
Dimensions: (W x D x H)	12.8 x 11.5 x 9 in.
Weight:	17.6 lbs / 8 kg
Electrical:	115 or 230V, 50-60 Hz
Warranty:	2 years





Ordering Information:

Item No.	Description:	
C5000-6H*	Sprint [™] 6H centrifuge with 6 x 10ml swing out rotor	
C5000-6H-PT*	Sprint [™] 6H portable kit, w/12V car adapter, leveling legs	
C3303-6HP*	Sprint [™] 6H PLUS centrifuge with 6 x 15ml swing out rotor	
C3303-1215	Optional 12 x 15ml fixed angle rotor (for C5000-6HP only)	
C5000-ADP	Optional adapters for 5ml & 7ml blood collection/culture tubes, 8/pk (Sprint 6H and 8)	
C3100-ADP	Optional adapters for 5ml & 7ml blood collection/culture tubes, 8/pk (Sprint 6H Plus)	

*115V with US plug. For 230V (EU plug), please add (-E).

Sprint 6H Pus

- Increased speed up to 4,000rpm / 2504xg
- Includes 6 place swing out rotor
- Adjustable speed control in rpm or rcf
 - Safety imbalance detection system
 - Optional 12 x 15ml fixed angle rotor (conical or round bottom)

Technical Data (Sprint 6H Plus):

` .	,
Speed Range:	200 to 4,000 rpm / 2,504 xg
Capacity:	6 x 15ml 6 x 5-7ml (13mm) 12 x 15ml (fixed angle)
Speed Increment:	100 rpm
Timer:	10 sec. to 99h 99 min. / cont.
Momentary:	Yes
Dimensions: (W x D x H)	12 x 16 x 10.5 in.
Weight:	21 lbs / 9.5 kg
Electrical:	115 or 230V, 50-60 Hz
Warranty:	2 Years